



SpeedGleam™

specifications



Burnishing Models	SpeedGleam	SpeedGleam Plus
Transport mode	Pad assist forward motion	Self propelled, variable speed, continuous 0.2 hp transaxle
Main wheels	8 in / 203 mm (2) Non-marking	
Casters	3 in /76 mm (1) Non-marking	
Pad Motor	3 hp, 2.24 kW	
Pad Motor Speed	2000 rpm - nominal load / 2500 rpm - no load	
Pad pressure	Variable; 15-45 lb / 7-20 kg	
Pad driver	Flexible, full pad contact	
Productivity		
Maximum coverage rate per hour	21,000 ft² /h / 1951 m² /h	
Burnish width	20 in /508 mm	
Debris System		
Dust Control	Scrolled base design with dust shield for optimum air flow and dust control. Cloth filter bag, filters with 99.9% efficiency at 0.3 micron	
Power System		
Battery	(3) 12 V, 215 AH capacity batteries	
Battery run time per charge	Up to 2.4 hr continuous at nominal load up to 3 hr at minimum load	
Charging unit description	36 V DC, 25 A	
Optional Accessories		
Optional accessories	Flashing safety lights, safety key switch, auto stop button, parking brake, low battery shut-off, hour meter and power cut off while charging	
Dimensions / Weight / Sound level		
Length	52 in / 1320 mm	
Width	24 in / 610 mm	
Height	40 in / 1020 mm	
Net weight w/ batteries	543 lb / 250 kg	
Sound level (operator's ear)	70 dBa	
System design	Patented, free floating head for even gloss	
Warranty	3 years/2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene parts.	