



Frontier® specifications



Brush Drive System

Brush diameter	3.375 in / 85 mm
Brush motor RPM	1800 rpm
Brush RPM	1200 rpm

Vacuum System

Airflow through 2 in orifice	101 ft ³ / 2.86 m ³ /m
Vacuum motor amps	13 A
Vacuum motor hp	1.8 hp / 1.34 kW
Vacuum motor stages	3 stage
Vacuum motor watts	1560 watts
Waterlift at sealed orifice	137 in / 3480 mm

Solution System

Nominal solution flow rate	1 gpm / 3.75 L / min
Solenoid valve description	Electrically operated
Solution capacity	10 gal / 37.5 L
Spray jets count	5-quick disconnect

Recovery System

Recovery tank capacity	14.5 gal / 54.89 L
------------------------	--------------------

Productivity

Maximum coverage rate	3500 ft ² / h / 241.54 m ² / h
Cleaning width	20 in / 500 mm

Power System

Power consumption amps	14.2 A
Power consumption watts	1710 watts
Power cord length	50 ft / 23 m

Pump System

Solution pump pressure	100 psi / 7 kPa
------------------------	-----------------

Dimensions / Weight / Sound Level

Length	45 in / 1143 mm
Width	20 in / 500 mm
Height	34 in / 860 mm
Net weight	90 lb / 40.82 kg
Sound Level	80 dBA

Warranty

3 years/2500 hrs on parts and labor (excluding batteries).
10 years on rotationally-molded polyethylene tanks.