

**NOBLES®****Speed Scrub® 2001/2001E
specifications**

Models	SS 2001(Battery)	SS 2001E (Cord Electric)
Scrubbing System		
Cleaning path	20 in / 51 mm	
Solution tank capacity	10 gal / 38 L	
Productivity per hour	20,536 ft2 / 1,908 m2	
Solution flow rate variable to)	0.5 gpm / 1.89 lpm	
Scrub motor	0.75 hp / 0.56 kW	
Scrub motor speed	220 rpm	250 rpm
Brush / pad down pressure	50 lb / 22.68 kg	
Brush size (1)	20 in / 508 mm	
Recovery System		
Recovery tank capacity	12 gal / 45 L	
Vacuum fan Motor	0. 5 hp / 0.640 kW	1. 15 hp / 0.640 kW
Stages	2-stage	2-stage
Water lift	44 in / 1117.6 mm	82 in / 2082.8 mm
Power System		
Battery run time per charge (2)	Up to 2.5 hr	Power Cord
Power cord type	N/A	14 gauge, 3-wire SJTO yellow
Power cord length	N/A	75 ft/ 22.8 m
Dimensions / Weight / Sound level		
Length	47 in / 1194 mm	
Width body	22 in / 559 mm	
Width w/squeegee	30.25 in / 768 mm	
Height	38 in / 965 mm	
Net weight	280 lb / 127 kg	
Net weight w/batteries	238 lb / 108 kg	
Sound level (operator's ear)	70 dBa	70 dBa
Warranty		
3 years/2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene tanks.		