



Speed Scrub®

Cord-electric, 15" cylindrical scrubber specifications



Scrubbing System

Cleaning path	15 in / 380 mm
Solution tank capacity	3 gal / 11.4 L
Productivity (per hour)	
Theoretical max	15,920 ft ² / 1,480 m ²
Estimated actual*	8,690 ft ² / 810 m ²
Solution flow rate	0.10 gpm / 0.38 lpm
Scrub motor	0.4 hp / 0.3 kW
Scrub motor speed	2400 rpm
Brush down pressure	33 lb / 15 kg
Brush size	3.5 in / 89 mm

Recovery System

Recovery tank capacity	4.5 gallon / 17.0 liter (Includes demisting chamber)
Vacuum fan	
Motor	1.2 hp / .88 kW
Stages	2-stage
Water lift	86 in / 2180 mm
Airflow	99 cfm / 2.8 m ³ /min

Construction & Power System

Chassis Construction	Cast aluminum frame, rotational molded tanks and injection molded plastic cover
Power Supply	120V
Frequency	50 / 60 Hz
Cable Length	50 ft / 15 m
Electrical Safety Approvals	ETL Tested for UL & CSA Standards

Dimensions / Weight / Sound level

Length	
Handle in working position	45.4 in / 1150 mm
Handle in folded position	27.3 in / 690 mm
Width	
Base	19.7 in / 500 mm
Squeegee	17.5 in / 440 mm
Height	
Base (folded handle)	23.8 in / 600 mm
With Handle Up	34 in / 860 mm
Net weight	97 lb / 44 kg
Working weight (with water)	121 lb / 55 kg
Sound level** (operator's ear)	72 dBA

Warranty

3 years/2500 hrs on parts and labor.
10 years on rotationally-molded polyethylene tanks.
Please contact your Nobles representative for additional warranty details.

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA