

Speed Scrub® 500

Walk-Behind Scrubber

Powerful Levels of Clean

Clean virtually any hard surface condition to maximize return on investment with a wide range of cleaning options and configurations. The reliable Speed Scrub® 500 Walk-Behind Scrubber provides the right solution for your application with its versatile design, easy to use controls and durable components.

Available Technologies

-  Lithium-Ion Batteries
-  IRIS® Asset Manager
-  ec-H2O NanoClean® technology



Effective Cleaning

Clean virtually any hard surface condition with three scrub head options, including orbital.



Innovative Features

Help keep floors dry with redesigned squeegee and integrated P-trap that improves water pick-up and prevents water drips after cleaning.



Reliable Performance

Extend machine life and reduce costs with durable components.

Inside the **Speed Scrub® 500**

1. Improve operator ergonomics with updated control panel that puts propel direction switch, speed settings, down pressure settings and water flow settings all within easy reach.

2. Maximize battery productivity with Smart-Fill™ technology, an optional on-board, virtually no-hassle battery watering system.

3. Easy daily maintenance with yellow touch points to help reduce breakdowns.

4. Evenly and effectively remove floor finish with high orbital downpressure and durable isolators.



Speed Scrub® 500 specifications

FEATURE	SPECIFICATION				
	DUAL DISK			CYLINDRICAL	ORBITAL
Cleaning Path	26 in / 650 mm	28 in / 700 mm	32 in / 800 mm	28 in / 700 mm	28 in / 710 mm
Productivity Theoretical Max (per hour)	28,600 ft ² /hr / 2,657 m ² /hr	30,800 ft ² /hr / 2,861 m ² /h	35,200 ft ² /hr / 3,270 m ² /hr	30,800 ft ² /hr / 2,861 m ² /h	30,800 ft ² /hr / 2,861 m ² /hr
Brush RPM	220 rpm			1500 rpm	2200 rpm
Brush/Pad Pressure - Low High	65 lbs / 29.5 kg 120 lbs / 54.5 kg	70 lbs / 32 kg 120 lbs / 54.5 kg	75 lbs / 34 kg 120 lbs / 54.5 kg	85 lbs / 38.5 kg 120 lbs / 54.5 kg	110 lbs / 50 kg 170 lbs / 77 kg
Solution Tank Capacity	22.5 gal / 85 L			22.5 gal / 85 L	22.5 gal / 85 L
Recovery Tank Capacity	27 gal / 102 L			27 gal / 102 L	27 gal / 102 L
Battery Run Time - Wet 260AH or Lithium-ion 180AH (up-to hours)*	5.9		5.4	5.4	4.9
Battery Voltage	24 volt			24 volt	24 volt
LxWxH	58.5, 27.5, 43.3 in / 1,486, 700, 1,100 mm	59.1, 29.5, 43.3 in / 1,501, 750, 1,100 mm	61.1, 33.5, 43.3 in / 1,552, 850, 1,100 mm	59.1, 30.7, 43.3 in / 1,501, 780, 1,100mm	58.5, 28, 43.3 in / 1,486, 710, 1,100 mm
Weight (with battery)	610 lbs / 277 kg	620 lbs / 281 kg	645 lbs / 293 kg	660 lbs / 299 kg	660 lbs / 299 kg
Sound Level**	67.4 dBA			68.3 dBA	66.9 dBA

Specifications subject to change without notice.

* Up to run-times are based on continuous scrubbing run-times, 260AH batteries, low down pressure, ec-H2O off.

** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA.

For a demonstration or additional information, call **+1.800.553.8033** or email **info@tenantco.com**

Tennant Company
 10400 Clean Street
 Eden Prairie, MN 55344-2650, USA
 USA/Canada: +1.800.553.8033
 Quebec: +1.800.361.9050
 Overseas: +1.763.540.1315