



# Typhoon® 16 B

## specifications



<b>Vacuum System</b>	
Airflow at orifice	70 cfm / 1.98 m <sup>3</sup> / h
Vacuum motor amps	23 A
Vacuum motor diameter	5.7 in / 144.8 mm
Vacuum motor horsepower	0.75 hp
Vacuum motor stages	3 stage
Vacuum motor type	bypass
Vacuum motor voltage	24 V
Vacuum motor watts	566 watts
Waterlift at sealed orifice	70 in / 1778 mm

  

<b>Debris Recovery System</b>	
Filter description	Includes one cloth & one paper bag
Recovery tank wet capacity	16 gal / 60.57 L
Vacuum hose length	10 ft / 3.05 m

  

<b>Productivity</b>	
Maximum coverage rate per hour	20,000 ft <sup>2</sup> / h / 1858 m <sup>2</sup> / h

  

<b>Power System</b>	
Run time on full charge	4 Hours

  

<b>Optional Accessories</b>	
Optional accessories	16 in / 6.4 mm floor tool with adjustable brush, two-bend aluminum wands, 4 in / 101.6 mm upholstery tool, 11 in / 279.4 mm plastic crevice tool, 3 in / 76.2 mm round dusting brush, 14 in / 355.6 mm forward / reverse squeegee Typhoon 39 in / 990.6 mm, 33 inch / 838.2 mm and 26 inch / 660.4 mm front mount squeegee kits, wet recovery bag, 16 in / 406.4 mm wet pick-up kit, contractor tool kit and 11in / 279.4 mm dry tool kit, two 105 A 12-volt or two 130 A 12-volt batteries, 15 A battery charger.

  

<b>Dimensions / Weight / Sound level</b>	
Length	33 in / 838.2 mm
Width	21 in / 533.4 mm
Height	43 in / 1092.2 mm
Net weight	90 lb / 40.82 kg

  

<b>Warranty</b>	
	3 years / 2500 hrs on parts and labor (excluding batteries). 10 years on rotationally-molded polyethylene tanks.

\* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.  
\*\* Run times are based on Continuous Scrubbing Run Times.  
\*\*\* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA