



Viper® specifications



Vacuum System	
Airflow at 2 in orifice	125 cfm / 3.54 m ³ /h
Vacuum motor hp	1 hp
Vacuum motor type	Through flow, single stage; thermal protected
Vacuum motor watts	915 watts (7.9 amps)
Waterlift at sealed orifice	80 in / 2030 mm
Brush Drive System	
Brush belt description	Dual, round drive belts
Brush type	Single row, chevron pattern
Brush size	57 mm /2.25 in diameter; 305 mm /12 in length
Brush motor Hp	0.1 hp
Brush motor RPM	6000
Brush RPM	3000
Brush height	Adjustable to 6 positions with manual dial
Filtration	
Triple filtration system	Filter bag, vac motor filter, and post filter
Triple filtration description	High efficiency (99.9%) at 0.3 micron
Vacuum bag capacity	Top fill design; 5 L /5.2 qt
Vacuum hose length	0.46 m /1.5 ft (4:1 stretch ratio)
Electrical	
Electrical system	Printed circuit board protected
Indicator light	Multi - Signal light system for improved safety
Power cord length	40 ft/ 12 m
Accessories	
Standard	On-board crevice tool, swivel wand and flex hose
Optional	Dusting brush, wall and upholstery tool
Dimensions/Sound level	
Height	47 in / 1190 mm
Length	14.5 in / 368 mm
Weight	Approx. 21 lb / 9.53 kg
Width	14 in / 356 mm
Sound level	69.5 dBA
Warranty	
	1 year on parts and labor