

Dual Motor Upright Vacuum



Lightweight handle, quiet operation, and powerful pickup – the V-DMU-15 has it all!

Powerful

Combined heavy-duty, 2-stage vac motors and vigorous 5,000 rpm brush speed ensure maximum cleaning performance on the first pass.

Cost effective

Reduce maintenance costs and downtime with “no tools needed” brush replacement.

Reduce operator fatigue

Easily clean hard-to-access areas with convenient on-board tools and telescopic wand.

Key Benefits

- Clean longer and more comfortably with lightweight handle
- Proven performance as certified by CRI Seal of Approval Bronze level performance
- Clean areas quietly with OSHA recognized 69 dBA



Dual Motor Upright Vacuum



Features	Specifications*
Product Name	V-DMU-15
Vacuum System Airflow at 2 in / 50 mm orifice Vacuum motor hp Vacuum motor type Water lift at sealed orifice	92 cfm / 42L / sec 1.07 hp / 0.8 kW Two stage 79 in / 2000 mm
Brush Drive System Brush belt description Brush type Brush motor Brush speed Brush size Brush height	Cogged / gear drive belt Chevron bristle 180 Watts 5000 rpm 2.25 / 57 mm in diameter, 12 in / 305 mm length Operator adjustable
Filtration Five level filtration system Triple filtration description Vacuum bag capacity	3-ply filter bag, washable foam intake filter, 3M Filtrete®, vac motor filter High efficiency (98%) at 0.3 micron Fill design, 1.2 gal. / 4.5 L
Electrical Power cord length	41 ft / 12.5 m, 3 wire commercial safety-yellow cord with thermal protection switch
Chassis/Body Construction Construction	Injection molded Bayblend® (ABS and polycarbonate) and ABS
Accessories Standard	On-board crevice tool, dusting brush with telescopic aluminum wand
Dimensions/Weight/Sound Level Length Width Height Weight Sound level (at operator's ear)	13 in / 330 mm 15 in / 380 mm 44 in / 1120 mm 18.2 lb / 8.3 kg 69 dBA
Approvals	UL
Warranty	See your sales representative or authorized distributor for complete warranty details.

*Specifications subject to change without notice