

INDEPENDENCE BATTERY LIGHT-WEIGHT UPRIGHT VACUUM



Combining an ultra-light vacuum with lithium ion technology.

Drop the cord

An upright lightweight vacuum without cords! No more hassles with cords or looking for outlets with this lithium-ion powered vacuum.

Increased ease of use

Easily transportable 11lb/5kg vacuum easily maneuvers and transports to help minimize operator fatigue. Clean a variety of floor types with automatic height adjustment.

Clean Anytime

Clean in more spaced anytime without cords in the way of people, a low dBA rating below 70 and an LED light for hard-to-see dark places.

Key Product Features

- Automatic pile height adjustment adapts to any floor type and reduces brush wear.
- Impressive 50 minute runtime to maximize productivity.
- Interchangeable battery allows operator to keep cleaning with ease.



1.628.001.am.en Independence Sell Sheet 02/18

©2018 The Tennant Company logo and other trademarks designated with the symbol "®" are trademarks of Tennant Company registered in the United States and/or other countries. Tennant Company's products are sold and serviced through subsidiaries of Tennant Company and distributors. All rights reserved.

Nobles
701 North Lilac Drive
Minneapolis, MN
55422 USA

USA/Canada:
+1.800.553.8033
Quebec:
+1.800.361.9050
Overseas:
+1.763.540.1315

www.nobles.com
nobles@tennantco.com

INDEPENDENCE BATTERY LIGHT-WEIGHT UPRIGHT VACUUM



FEATURES	SPECIFICATIONS*
Product Name	Independence
Vacuum System Airflow at 2 in / 50 mm orifice, high speed Vacuum motor watts Vacuum motor type Vacuum motor amps	50 - 60 cfm / 1.4 - 1.7 m ³ /m 153W Single stage, thermal protected, direct air 3.5A
Brush Drive System Brush belt description Brush type Brush size Brush height	Flat round drive belt 13 in / 330 mm metal brush roll with white crimped bristles 2.125 in / 53.2 mm in diameter Automatic, self adjusting
Filtration Filtration system Filtration description Vacuum bag capacity	HEPA paper bag High efficiency (99.97%) at 0.3 micron Fill design, 7.66 qt / L 7.25
Power Source Power Source Interchangeable battery pack Run time Charge time	44VDC / 2.9 Ah lithium ion battery Yes Up to 50 minutes ≤ 2 hours
Chassis/Body Construction Construction	Injection molded ABS
Dimensions / Weight / Sound Level Length Width Height Weight Sound level (at operator's ear)	13 in / 330 mm 10 in / 254 mm 44.5 in / 1130.3 mm 11 lb / 4.99 kg ≤ 70 dba
Approvals*	UL (Canada/US)
Warranty	See your sales representative or authorized distributor for complete warranty details.

*Specifications subject to change without notice and will vary throughout the operation of the machine; averages are shown.
UL does not rate these machines in amperage or wattage.