



NOTES:

1. SPECIFIED MANUFACTURER: BERGQUIST
MANUFACTURER'S MATERIAL SPEC: 1000VOUS (TACKY ON FRONT SIDE SHOWN)
MANUFACTURER'S PART NUMBER: GPVOUS-0.100-01-0816

2. THICKNESS 2.54 mm [0.100 in]
REFERENCE THICKNESS TOLERANCE: +/- 10 %
+/- 0.254 mm [0.010 in]

3. REFERENCE MATERIAL SPECIFICATIONS:
THERMAL CONDUCTIVITY: 1.0 W/m-k
OPERATING TEMPERATURES: -60 C TO +200C
THERMAL IMPEDANCE: 1.97 C- IN^ 2/W @ 10% DEFLECTION
DIELECTRIC BREAKDOWN VOLTAGE (VAC) = 6,000
HARDNESS SHORE 00: 5
FLAME RATING: V - 0

MATERIAL SPECIFICATIONS: NOTED	OTHER TREATMENTS AND FINISHES NONE	PAINT - COLOR NONE
PART NAME: PAD, THERMAL, SILICONE [TBR3206]	GLOSS	PERFORMANCE

CHANGED BY: BEN THORUD	DATE: 12/20/2023	DES: RYAN WALDMANN
MDR:		
ACCEPTANCE		

WELDING NOTATION IN ACCORDANCE WITH AWS A2.4-98			
REV	ECO		
00	39394		
UNLESS OTHERWISE SPECIFIED DIMENSION TOLERANCING IN ACCORDANCE WITH ASME Y14.5-2009 ALL UNTOLERANCED DIMENSIONS ARE CONTROLLED BY:			
X.X	±1.5	±[.06]	
X.XX	±0.75	±[.030]	
X.XXX	±0.250	±[.0098]	
ANGLES	±2.0°		

GENERAL NOTES	
PRIMARY DIMENSIONS ARE METRIC, REFERENCE DIMENSIONS WITH BRACKETS ARE INCH. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE AFTER TREATMENTS AND FINISHES.	
PROPRIETARY INFORMATION	
MAY NOT BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT WRITTEN PERMISSION OF TENNANT COMPANY.	
SHEET 1 OF 1	

DWG C SIZE	PART NUMBER 1261002