



Model 1240 Specifications

CARPET EXTRACTOR

Feature	English / Metric
Brush Drive System	
Brush bristle type	Offset rows of nylon bristles in a chevron pattern
Brush diameter	3.31 in / 84 mm
Brush length	13 in / 330 mm
Brush motor amps	1.5 amp
Brush motor power	0.25 hp / 0.18 kW
Brush RPM	1,380 rpm
Motor RPM	2,300 rpm
Chassis/Body Construction	
Chassis construction	Rotationally-molded polyethylene
Metal parts coating	Zinc plating with yellow chromate
Wheel descriptions	Non-marking gray tread
Recovery System	
Airflow at 2-inch (50 mm) orifice	95 ft ³ / min / 345 m ³ /min
Vacuum motor power	1.8 hp / 1.34 kW
Vacuum motor stages	3 stage
Vacuum motor amps	13 A max
Recovery capacity	14.5 gallon / 55 liter
Sealed waterlift	136 in / 3454 mm
Machine Dimensions	
Length	43 in / 1092 mm
Machine Width	16 in / 406 mm
Height	34 in / 863 mm
Weight	104 lb / 47.5 kg
Solution System	
Solution tank capacity	10 gallon / 38 liter
Solution pump amps	1 amp
Solution pump pressure	100 psi / 690 kPa
Pump flow rate	1 gpm / 3.8 L/min
Solution valve	Electric solenoid
Spray jet count	Dual, quarter turn with large grip
Power Consumption	
Amps	14.5 amps
Voltage	120 VAC
Watts	1740 watts
Power Cord	
Power cord length	50 ft / 15.24 m, detachable
Power cord type	16 gauge, safety yellow
Sound Level	
Decibel rating at operator's ear	78 dBA