



REINVENT HOW THE WORLD CLEANS



# T981

## Ride-On Floor Scrubber

### Maneuverable and Productive

T981 effectively scrubs and dries large hard-floor surfaces with light to medium dirt and stains. Its intuitive controls make it easy to operate and maintain. T981 is ideal for cleaning smooth floors in areas such as retail, logistics and light industry.



### Productivity Boost

Easily fit into the most congested spaces with narrow turning radius and get more cleaning done with the lead acid batteries that allow cleaning shifts up to 6 hours.



### Simple Operation

Easy start-up and quick training with three pre-set cleaning programs that allow operator to choose whichever program best fits their soil level.



### Get the Right Solution

Choose between the 36 inch / 90 cm disk or 30 inch / 75 cm cylindrical scrub deck to fit T981 into your application.

# Inside the T981

1. **Easily change water flow rate** and other cleaning functions from intuitive control panel.
2. **Enhance facility image and safety** by recovering more water with high-performance 3-stage vacuum motor.
3. **Quick, mess-free tank draining** with large, pinch-style recovery tank drain hose.
4. **Large solution tank** with level gauge and drain hose.
5. **Consistent water pick-up** with durable parabolic squeegee design and standard Linatex® squeegee blades.
6. **Simple no-tools, no-touch brush change system.**



## T981 Specifications

FEATURE	SPECIFICATION	
	DISK	CYLINDRICAL
Cleaning path	36 in / 90 cm	30 in / 75 cm
Productivity theoretical max	57,048.7 ft <sup>2</sup> /hr / 5,300 m <sup>2</sup> /hr	46,284.8 ft <sup>2</sup> /hr / 4,300 m <sup>2</sup> /hr
Estimated coverage*	42,517.5 ft <sup>2</sup> /hr / 3,950 m <sup>2</sup> /hr	33,368.1 ft <sup>2</sup> /hr / 3,100 m <sup>2</sup> /hr
Scrubbing speed	3.7 mph / 6 kmh	
Scrub head and squeegee raise/lower	independent actuators	
Brush speed	200 rpm	1000 rpm
Brush pressure	220.5 lbs / 100 kg	110.2 lbs / 50 kg
Solution tank capacity	33 gal / 126 L	
Recovery tank capacity	36 gal / 135 L	
Battery run time - up-to hours (360Ah Wet Battery)**	6.4	
Battery voltage	36V 1x 36V or 6 x 6V	
Dimensions (LxWxH)	67.7 x 43.3 x 53.5 in / 1,720 x 1,100 x 1,360 mm	71.3 x 41.3 x 53.5 in / 1,810 x 1,050 x 1,360 mm
Squeegee width	43.3 in / 1,100 mm	39.8 in / 1,010 mm
Weight (with heaviest battery)	1,558.7 lbs / 707 kg	1,576.3 lbs / 715 kg
External radius (wall to wall)	90.9 in / 2,310 mm	95.7 in / 2,430 mm
Maximum climbing angle	9° / 16%	
Sound level (operator's ear)***	72 dB	

Specifications subject to change without notice.

\* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

\*\* Run times are based on Continuous Scrubbing Run Times.

\*\*\* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

For a demonstration or additional information,  
call **+1.800.553.8033** or email **info@tennantco.com**

1981-brochure-en-noam 6/25 ©2025 The Tennant Company.

**Tennant Company**  
10400 Clean Street  
Eden Prairie, MN 55344-2650, USA  
USA/Canada: +1.800.553.8033  
Quebec: +1.800.361.9050  
Overseas: +1.763.540.1315  
[www.tennantco.com](http://www.tennantco.com) | [info@tennantco.com](mailto:info@tennantco.com)