

T350 | Stand-on Scrubber Competitive Comparisons

Product Specifications

		Tennant T350 20" (50 cm)	Tennant T350 24" (60 cm)	Windsor/Karcher Chariot 2 iScrub 20 20: (cm)	Nilfisk SC1500 20" (cm)	Windsor/Karcher Chariot 3 iScrub 26 Deluxe
Feature						
Cleaning Path	Inches mm	20 in 500 mm	24 in 600 mm	20 in 508 mm	20 in 510 mm	26 in 664 mm
Conventional Practical Productivity*	ft ² /hr m ² /hr	24,588 2,287	30,052 2,295	14,304 1,330	17,160 1,600	27,639 2,570
Solution Tank Size	Gallons Liters	14.1 53	14.1 53	10.0 38	12.0 45	25 95
Recovery Tank Size	Gallons Liters	18.4 70	18.4 70	10.0 38	12.5 47	28 106
Machine Speed	mph km/hr	3.6 5.8	3.6 5.8	2.7 4.3	2.6 4.2	4.1** 6.5**
Brush/Pad Speed	RPMs	215	275	180	140	300
Brush/Pad Down Pressure	Lbs kg	62 and 90 28 and 41	64 and 91 29 and 41	50 lbs 23 kg	51 and 75 23 and 34	75 - 100 34 - 45
Conventional Solution Flow Rate	gpm lpm	0.15 / 0.35 / 0.50 0.57 / 1.32 / 1.89	0.15 / 0.35 / 0.50 0.57 / 1.32 / 1.89	0.33 1.25	0.16 / 0.35 / 0.50 0.60 / 1.3 / 1.9	Not Provided
Solution Tank Drain Time	Minutes	94	94	30	75	NA
Sound Level - Standard	dBA	63.7	64.5	66.9	63	66
Reduced Sound Level		59.7	61.3			
Battery Run Time	Hours	3.1	4.0	Not Provided	Not provided	Not Provided
Turning Radius	Inches mm	60 1524	60 1524	48 1219	59.5 1511	60 1524
Length X Width X Height	Inches mm	55 X 26.5 X 49 1,397 X 673 X 1,245	55 X 26.5 X 49 1,397 X 673 X 1,245	42 X 26.5 X 50.75 1,067 X 673 X 1,289	48.5 X 24 X 52.5 1,232 X 610 X 1,334	56.5 X 33 X 50 1,435 X 838 X 1,270
Weight (less batteries)	Lbs kg	490 222	495 225	209 96	NA	460 209
Weight (with batteries)	Lbs kg	725 329	730 331	Not Provided	620 281	Not Provided

Competitive Sources: manufacturers literature, operator manuals and website

* Based on Tennant calculations for practical productivity. Source for the Chariot 3 is provided Windsor/Karcher spec sheet.

** Karcher materials do not state if this is transport or scrub speed

Tennant Company Confidential - Internal Use Only