

## T350 | Stand-on Scrubber

### Product Specifications

Feature	20 in / 500 mm Single Disk Self Propel	24 in / 600 mm Dual Disk Self Propel
Cleaning Tool Attachment	Insta-Click™ Standard	
Machine Speed	5.8 km/hr (3.6 mph)	
Top Scrub and Forward Transport	1.8 km/hr (1.1 mph)	
Top Reverse Transport		
Scrubbing Coverage Rate Per Hour		
Theoretical Max	2,946 m <sup>2</sup> (31,680 ft <sup>2</sup> )	3,535 m <sup>2</sup> (38,016 ft <sup>2</sup> )
Conventional - Practical	2,287 m <sup>2</sup> (24,588 ft <sup>2</sup> )	2,795 m <sup>2</sup> (30,052 ft <sup>2</sup> )
ec-H2O NanoClean® - Practical	2,351 m <sup>2</sup> (25,284 ft <sup>2</sup> )	2,874 m <sup>2</sup> (30,903 ft <sup>2</sup> )
Control Panel		
Pro-Membrane™	Standard	
LCD Pro-Panel® Touch Screen	Optional	
Brush/Pad Drive System		
Cleaning Path	500 mm / 20 in	600 mm / 24 in
Pad/Brush RPM	215 rpm	275 rpm
Pad/Brush Down Pressure	28 & 41 kg (62 & 90 lbs)	29 & 41 kg (64 & 91 lbs)
Scrub Motor	24 VDC, 0.87 HP / 0.65 kW	
Solution and Recovery Systems		
Solution Tank Capacity	53 L (14.1 gal)	
Recovery Tank Capacity	70 L (18.4 gal)	
Drive Motor	24 VDC, 0.64 HP / 0.48 kW	
Vacuum Motor	24 VDC, 0.62 hp / 0.46 kW	
Vacuum Water Lift	1,067 mm (42 in)	
Cleaning Technology		
Conventional	Standard	
ec-H2O NanoClean® Technology	Optional	
Conventional Water Flow	0.57 / 1.32 / 1.89 lpm 0.15 / 0.35 / 0.50 gpm	
ec-H2O NanoClean® Technology	0.45 / 0.95 / 1.32 lpm 0.12 / 0.25 / 0.35 gpm	
Water Flow		

Feature	20 in / 500 mm Single Disk Self Propel	24 in / 600 mm Dual Disk Self Propel
<b>Battery System</b>		
System Voltage / Battery Count	24 Volts / 4	
Batteries	Wet 210 AH Wet 240 AH (Provides longest run time) Sealed AGM 220AH	
Battery Run Time (Up to Hours)	3.1	4.0
On-Board Charger	Yes	Yes
Off-Board Charger	Yes	Yes
<b>Decibel Ratings At Operator Ear</b>		
Standard - dBA	63.7	64.5
Quiet-Mode™ - dBA	59.7	61.3
<b>Machine Dimensions and Weights</b>		
Overall Width with Squeegee	765 mm / 30.1"	793 mm / 31.2"
Length X Width X Height	1,397 X 673 X 1,245 mm 55 X 26.5 X 49 Inches	
Weight (less batteries)	222 kg / 490 lbs	225 kg / 495 lbs
Weight (with batteries)	329 kg / 725 lbs	331 kg / 730 lbs
<b>Product Backing</b>		
Warranty	10 years Rotomold - 3 years Parts 2 years Labor - 6 months of Trip	