



CREATING A CLEANER, SAFER, HEALTHIER WORLD.



5700XP Specifications | Walk-Behind Floor Scrubber

Scrubbing System			
Cleaning path (3 paths available)	28-inch/700 mm	32-inch/800 mm	36-inch/900 mm
Solution tank capacity	30 gal/114 l		
Solution Flow Rate: Disk Standard	.22 gpm / .83 lpm		.30 gpm / 1.1 lpm
Cylindrical Standard & Disk Optional	.33 gpm / 1.25 lpm		.44 gpm / 1.66 lpm
Optional (Cylindrical & Disk)	.44 gpm / 1.66 lpm		.53 gpm / 2.0 lpm
Conventional Mode Optional	0-1.5 gpm / 0-5.7 lpm		0-1.5 gpm / 0-5.7 lpm
Scrub head types	Disk and cylindrical		
Scrub motors			
Disk	(2) 0.6 hp/0.45 kW	(2) 0.6 hp/0.45 kW	(2) 1.0 hp/0.75 kW
Cylindrical		(2) 0.75 hp/0.56 kW	
Brush speed		320 rpm/750 rpm	
Brush down pressure			
Disk		0-200 lb/0-91 kg	
HD disk (800 mm only)		0-300 lb/0-136 kg	
Cylindrical		0-90 lb/0-41 kg	
Brush/pad driver quantity & dimensions			
Disk (D)	(2) 14-inch/355 mm	(2) 16-inch/405 mm	(2) 18-inch/455 mm
Cylindrical (L x D)	(2) 28 x 6-inch/ 700 x 150 mm	(2) 32 x 6-inch/ 800 x 150 mm	(2) 36-inch/ 900 x 150 mm
Recovery System			
Recovery tank capacity	40 gal/151 l (Includes demisting chamber)		
Vacuum fan			
Motor		0.8 hp/0.6 kW	
Stages		3-stage	
Water lift		73-inch/1,855 mm	
Propelling System			
Propel speed (variable to)	3.1 mph/5.0 km/h		
Batteries (36 V system, charger included)			
Standard		(6) 6V, 235 AH	
Optional		(6) 6V, 335 AH	
Machine Dimensions / Sound level			
Length			
Disk		64-inch/1,625 mm	
Cylindrical		63-inch/1,600 mm	
Width		28.25-in/ 720 mm	
Body			
Scrub head			
Disk	30-inch/760 mm	34-inch/865 mm	38-inch/965 mm
Cylindrical	30.5-inch/775 mm	34.25-inch/870 mm	38.25-inch/970 mm
Squeegee	37.5-inch/950 mm	42-inch/1,070 mm	45.5-inch/1,160 mm
Height		43-inch/1090 mm	
Net weight			
Less batteries		415 lb/188 kg	
With batteries (6) 235 AH 6-V		817 lb/371 kg	
With batteries (6) 335 AH 6-V		1,021 lb/464 kg	
Minimum aisle turn:	66.25-inch/1,680mm	67-inch/1,700 mm	67.5-inch/1725mm
Sound level (operator's ear)	75 dBa		
Warranty	Please refer to your local Tennant representative for information.		

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Run times are based on Continuous Scrubbing Run Times.

*** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA