



CREATING A CLEANER, SAFER, HEALTHIER WORLD.

EQUIPMENT



T300

WALK-BEHIND FLOOR SCRUBBER-DRYER

- Delivering high performance, consistent results for virtually any hard surface condition while lowering cleaning costs

KEY T300 SCRUBBER-DRYER FEATURES BUILT ON COMMITMENT, COLLABORATION, SERVICE AND SUPPORT BY A CIRCLE OF EXPERTS SURROUNDING OUR CUSTOMERS



- **Onboard machine instructions** help ensure the machine is operated in a safe manner for better results, simplified training, and reduced cleaning costs.
- **Insta-Click™** patent-pending scrub-deck allows TennantTrue® pads and brushes to be installed ergonomically, resulting in a safer and faster installation.
- **Quiet-Mode™** reduces noise levels for daytime cleaning without disruption. Perfect for healthcare, education and office cleaning.
- **Orbital scrub-deck** delivers hassle free floor stripping, and deep grout cleaning.
- **Squeegee design** helps ensure dirt and soils are removed from the floor for minimum risk of slip-and-fall accidents and enables faster, easier installation of replacement TennantTrue® squeegee blades.
- **Easy fill port** makes filling the unit simpler, faster and reduces the chance of spills. The integrated hose clip keeps the hose in place allowing the operator to work on other tasks during the filling process.
- **Flow control valve** helps to control the flow rate when draining and reduces the risk of contact with dirty recovery water. It also decreases the need for secondary cleaning operations caused by spills.
- **Battery venting** with onboard charger fan and integrated venting allows the batteries to be charged safely with the lid closed.
- **Optimal down pressure and RPM** improves cleaning performance.
- **Accessory tray** allows you to keep the necessary cleaning supplies at hand, reducing trips to the cleaning cupboard.
- **Yellow touch points** helps simplify preventative maintenance and training, which prevents breakdowns.
- **New machine electronics** allow the machine to daily clean finished concrete surfaces and work with abrasive pads and brushes.
- **Zone Settings™** allow supervisors to easily set specific cleaning parameters for different applications. The saved cleaning programmes give the operators the flexibility to switch quickly from one setting to an other.

IMPROVE THE EFFECTIVENESS OF YOUR CLEANING RESOURCES, INVESTMENTS, AND OPERATIONS WITH NEW SUSTAINABLE TECHNOLOGIES.



THE T300 SCRUBBER-DRYER PROVIDES THE RIGHT SOLUTION FOR YOUR SPECIFIC APPLICATION WITH A VERSATILITY THAT IS UNMATCHED IN THE INDUSTRY.



REDUCED CLEANING COSTS

Improved and durable components extend machine life and reduces cost of ownership.



IMPROVE HEALTH AND SAFETY

Innovative features help protect health and safety of your operator, building occupants and the environment.



ENHANCE PREMISES IMAGE


Effective scrubbing capabilities help to maintain a consistently clean appearance of your premises floors.



MINIMISE ENVIRONMENTAL IMPACT

Use of ec-H2O NanoClean™ reduces the consumption of daily floor cleaning detergents to help meet your sustainability goals.

INSIDE THE T300



ec-H2O NanoClean™ with optional Severe Environment™ Switch eliminates secondary cleaning operations that could increase slips and falls.

Quiet-Mode™ reduces noise levels for daytime cleaning without disruption. Perfect for healthcare, education and office cleaning.

KEY OPTIONS



ENGINEERED FOR PRODUCTIVITY AND VERSATILITY

INNOVATIVE TECHNOLOGY THAT SUPPORTS MULTIPLE CLEANING NEEDS IN YOUR PREMISES

The T300 scrubber-dryer provides multiple scrub-decks to fit your cleaning requirements and optimise cleaning performance.




EXCLUSIVE EC-H₂O NANOCLEAN™ TECHNOLOGY



Electrically converted water is created by an onboard e-cell that generates millions of microscopic bubbles known as nanobubbles that promote the cleaning efficacy of the solution.

This next generation solution now cleans better and cleans more soils in more applications, thanks to the nano-scale bubbles that are an important part of the cleaning mechanism.



Optional Pro-Panel™ integrates an LCD touchscreen with easy to understand graphics, multilingual menus, operator ID and video tutorials.

The T300 along with the 3M™ High Shine pads provides a complete floor care process that restores the natural beauty of your porous stone and produces a remarkable, long-lasting shine.



3M™ High Shine Pads

T300 WALK-BEHIND FLOOR SCRUBBER-DRYER

	SINGLE DISK		SINGLE DISK		DUAL DISK	CYLINDRICAL	ORBITAL
	430 MM PAD ASSIST	430 MM SELF-PROPEL	500 MM PAD ASSIST	500 MM SELF-PROPEL	600 MM SELF-PROPEL	500 MM SELF-PROPEL	500 MM SELF-PROPEL
Productivity (per hour)							
Theoretical max	1,579 m²		1,858 m²		2,230 m²	1,858 m²	1,858 m²
Estimated coverage*							
Conventional	868 m²	1,157 m²	1,041 m²	1,388 m²	1,697 m²	1,388 m²	1,388 m²
ec-H2O NanoClean™	898 m²	1,198 m²	1,078 m²	1,437 m²	1,756 m²	1,437 m²	1,437 m²
BRUSH DRIVE SYSTEM							
Scrub motor	24 VDC, 0.75 kW		24 VDC, 0.75 kW		24 VDC, 0.75 kW	24 VDC, 0.75 kW	0.45 kW
Brush/pad RPM	230 rpm		230 rpm		285 rpm	1,065 rpm	2,200 rpm
Dual Down Pressure	21,39 kg		23,41 kg		26,44 kg	24,29 kg	29,50 kg
Actuated Down pressure	21, 32, 39 kg		23, 35, 41 kg		26, 37, 44 kg	24, 27, 29 kg	29, 42, 49 kg
SOLUTION/RECOVERY SYSTEM							
Solution tank capacity	42 L		42 L		42 L	42 L	42 L
Recovery tank capacity	53 L		53 L		53 L	53 L	53 L
Vacuum motor	24 VDC, 0.45 kW		24 VDC, 0.45 kW		24 VDC, 0.45 kW	24 VDC, 0.45 kW	24 VDC, 0.45 kW
Vacuum waterlift	1067 mm		1067 mm		1067 mm	1067 mm	1067 mm
Vacuum waterlift with Quiet-Mode™	711 mm		711 mm		711 mm	711 mm	711 mm
CLEANING TECHNOLOGY							
Conventional	Standard		Standard		Standard	Standard	Standard
ec-H2O NanoClean™ Technology	Optional		Optional		Optional	Optional	Optional
Severe Environment™ (with ec-H2O NanoClean™)	Optional		Optional		Optional	Optional	Optional
Severe Environment™ detergent tank	1.5 L		1.5 L		1.5 L	1.5 L	1.5 L
BATTERY SYSTEM							
System voltage	24 volt		24 volt		24 volt	24 volt	24 volt
Battery types							
(Wet 120AH with Battery Fill System, Sealed Gel 76AH, Sealed Gel 105AH, Sealed Gel Fast Charge 60AH)	2 required		2 required		2 required	2 required	2 required
Battery run time (up to hours)	3,0	2,8	2,5	2,4	2,2	1,9	3,1
Onboard charger	Optional		Optional		Optional	Optional	Optional
Offboard charger	Optional		Optional		Optional	Optional	Optional
MACHINE SPECIFICATIONS							
Length	1,302 mm		1,372 mm		1,314 mm	1,283 mm	1,245 mm
Width	500 mm		559 mm		660 mm	635 mm	521 mm
Height	1,095 mm		1,095 mm		1,095 mm	1,095 mm	1,095 mm
Weight (without batteries)	98 kg	104 kg	104 kg	109 kg	113 kg	113 kg	116 kg
Weight (with batteries)	166 kg	177 kg	171 kg	181 kg	186 kg	186 kg	188 kg
Sound level (operator's ear)**	64.9 dBA		64.9 dBA		66.5 dBA	65.6 dBA	66.4 dBA
Quiet Mode (operator's ear)	57.8 dBA		57.8 dBA		59.1 dBA	to be determined	57.6 dBA

WARRANTY

See your local representative for warranty information

* Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.

** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment manufacturers & OSHA.

Subject to change without notice.

SEEING IS BELIEVING

For a demonstration or additional information contact us:

TENNANT UK CLEANING SOLUTIONS LTD
Gladstone Road
Northampton NN5 7RX
UNITED KINGDOM
Tel: 0800 111 4402 (local rate UK only)
Tel: 01604 583191
Fax: 0845 052 9349
E-mail: sales.uk@tennantco.com
E-mail: enquiries@tennantco.com
Internet: www.tennant.uk

TENNANT EUROPE NV
Roderveldlaan 3
2600 Antwerp
BELGIUM
Tel: +32 3 217 94 11
Fax: +32 3 217 94 19
E-mail: europe@tennantco.com