



## **T360**

# Mid-size walk-behind scrubber

#### Cleaning made easy

The T360 provides a simple and versatile solution for cleaning in a variety of spaces. Featuring easy-to-use controls for quick, straight-forward operation and a 70 cm scrub head for exceptional productivity.



#### Highly maneuverable

Clean a variety of spaces with an easy-to maneuver design allowing operators high viability.



Water recovery

Parabolic squeegee design provides excellent water recovery.



Maintenance free batteries

Up to 3-hour battery life on a single charge.

### Inside the T360

- 1. Excellent water pick**up** and featuring a parabolic squeegee design with standard Linatex® blades.
- 2. Straightforward operation with easyto-use self-propel controls.
- 3. Simple to clean out with easy access and visibility into the tanks.
- 4. Floating splash guard controls water spray to maximize water pickup, helping to keep floors dry.
- 5. Magnetic assisted brush/pad change out system.
- 6. Easy daily maintenance with yellow touch points to help reduce breakdowns.



## T360 Specifications

FEATURE	SPECIFICATION
Cleaning path	28 in / 700 mm
Productivity (per hour) theoretical max	31,645.9 ft <sup>2</sup> / 2,940 m <sup>2</sup> /hr
Brush/pad speed	180 rpm
Brush/pad pressure	66 lbs / 30 kg
Solution tank capacity	18.5 gal / 70 L
Recovery tank capacity	20 gal / 75 L
Battery run time - up-to hours*	3 hrs
Battery voltage	24 volt
Dimensions (L x W x H)	52.6 x 29.5 x 44.5 in / 1,335 x 750 x 1,130 mm
Squeegee width	38.3 in / 973 mm
Weight (with standard batteries)	402.1 lbs / 182.4 kg
Sound level**	69 dB

 $Specifications \ subject \ to \ change \ without \ notice.$ 

For a demonstration or additional information, call +32 3 217 94 11 or email europe@tennantco.com

t360-brochure-en-emea

<sup>\*</sup>Run times are based on Continuous Scrubbing Run Times.

<sup>\*\*</sup> Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA