

T600 vs 5680 Comparison



CATEGORY	T600 Disk/Cylindrical	T600 Orbital	5680 Disk/Cylindrical
Scrub Head Type/Size	Disk: 700mm, 800mm, 900mm Cylindrical: 700mm, 800 mm	Orbital: 700 mm	Disk: 700mm, 800 mm, 900 mm Cylindrical: 700 mm, 800 mm, 900 mm
Solution Tank Capacity	121L		114L
Solution Tank Orientation	Bottom tank		Top tank
Solution Tank Auto Fill	Standard		No
Recovery Tank Capacity	140L		151L
Recovery Tank Orientation	Top tank		Bottom tank
Optional Tank Rinse Out	Optional Pumped System with Spray Nozzle and Hose		No
Run-time* (up-to hours)	700mm/800mm disk: 5.1, 900mm disk: 5.0 700mm cylindrical: 7.3, 800mm cylindrical: 6.1	6.2	4.5 with 335 AH
Controls - Down Pressure/ Water Flow	Zone Settings™ Capability DP Settings: 3 WF Settings: 4		DP Settings: Variable WF Settings: Variable
Optional Smart-Fill™ Automatic Battery Watering	Have confidence batteries are watered with a virtually worry-free, optional on-board system with low tank alert (only for West 180AH).		No
Optional Severe Environment™ Switch	Optional on ec-H2O NanoClean® machines		No
Battery Compartment Controlled Flow	Yes		No
Squeegee	Improved water pick-up design. Foot activated with new integrated p-trap.		Hand activated with hose-style p-trap.
Brush/Pad Down Pressure	700mm, 800mm, 900mm disk: Low 45kg / Medium 68kg / High 90kg 700mm, 800mm cylindrical: Low 23kg / Medium 32kg / High 41kg	Low: 48kg Medium: 61kg High: 77kg	Disk: Low 45.5kg / High 91kg Cylindrical: Low 39kg
Brush/Pad RPMs	Disk = 300 Cylindrical = 760	Orbital = 2,200	Disk = 200 Cylindrical = 750



REDUCE COSTS TO CLEAN, increase productivity and simplify operator training with the T600's suite of innovative technologies, such as ec-H2O NanoClean® technology and IRIS® Asset Manager.



UPDATED ERGONOMIC CONTROLS

Easily and ergonomically adjust speed control and propel direction, and change the amount of water flow with a touch of a button.



SMART-FILL™ AUTOMATIC BATTERY WATERING

Maximize battery productivity with the exclusive patent-pending Smart-Fill™ technology. Eliminate the need for operators to check, open or fill batteries with an on-board, virtually worry-free battery watering system. (Optional feature)



REDESIGNED SQUEEGEE

Reduce the risk of slips and falls with a redesigned squeegee that improves water pick-up and allows for easier installation of squeegee blades. Features an integrated p-trap that prevents water from dripping on the floor after cleaning.

*T600 run-time based on 210AH optional battery dual-disk head, ec-H2O off, and low down pressure.

EN 60335-2-72 © 2018 The Tennant Company. All rights reserved. Specifications are subject to change without notice.