



X6 ROVR™ SPECIFICATIONS

AUTONOMOUS FLOOR SCRUBBER

Operating system	BrainOS®
Learning type	Teach and Repeat and Area Fill
Scrubbing path	26 in / 650 mm dual disk
Estimated coverage per solution tank	75.000 ft ² / 6.967 m ²
Squeegee	32.9 in / 835 mm
Solution tank	25 gal / 95 L
Recovery tank	25 gal / 95 L
Demisting chamber	3.4 gal / 13 L
Brush/pad rpm	220 rpm
Brush/pad downforce	up to 120 lbs / 54 kg
Battery	Lithium-Ion, 180 Ah
Cleaning tool attachment	Insta-Click®
Autonomous scrubbing battery time	Up to 6 hours
Autonomous solution delivery system	Velocity-controlled
Conventional scrubbing - pumped solution flow rates	Low: 0.09 - 0.21 GPM / 0.34 - 0.78 LPM Med: 0.09 - 0.25 GPM / 0.34 - 0.93 LPM High: 0.09 - 0.31 GPM / 0.34 - 1.17 LPM
Charger type	on-board, optional Tennant XC ¹ charging station
Charger specs	50/60Hz, 100-240 VAC
System voltage	25.6 volts
Vacuum motor	0.6 hp / 0.45 kW
Standard sound level	as low as 69dBA
Aisle navigation	as low as 104 cm
Aisle entrance (90 degree)	as low as 119 cm
Aisle u-turn	as low as 152 cm
Machine height	46 in / 117 cm
Machine length	48 in / 121 cm
Machine width	31.5 in / 80 cm
Autonomous distance to wall	as low as 7.6 cm
Weight (tanks empty, with battery)	582 lbs / 264 kg

For a complete selection of genuine Tennant parts, brushes and pads, please consult the X6 ROVR Parts and Consumables Reference Guide