



CREATING A CLEANER, SAFER, HEALTHIER WORLD.

S10 with HEPA Dust Control Specifications Battery-Powered Walk-Behind Sweeper

SWEEPING SYSTEM

Type Direct-throw Cleaning path 26 in | 660 mm Coverage rate per hour Average (full speed, 2 in (5 cm) overlap) 30,000 ft² | 3,800 m² Maximum (full speed, no overlap) 33,200 ft² | 3,080 m² Main brush length (tubular) 26 in | 660 mm Main brush change No-tool Brush speed 550 rpm Hopper volume capacity 2.8 ft³ | 79 L Hopper weight 150 lb | 68 kg Hopper dump Mechanical lever or lift-and-dump

PROPELLING SYSTEM

 $\begin{array}{lll} \mbox{Propelling motor} & 1.0 \ \mbox{hp} \mid 0.75 \ \mbox{kW} \\ \mbox{Propel speed forward (variable to)} & 2.9 \ \mbox{mph} \mid 4.7 \ \mbox{km/h} \\ \mbox{Propel Type} & 2.9 \ \mbox{mph} \mid 4.7 \ \mbox{km/h} \\ \mbox{Chain drive differential} \\ \mbox{Gradeability} & \end{array}$

Empty hopper 7.0 deg/12.2%
Full hopper 5.0 deg/8.75%
Tires front (2), semi-pneumatic 2x10 in | 51x250 mm
Tire rear (1), solid caster 1.5 x5 in | 38x130 mm
Batteries 24V system, 2x12V 155Ah

OPERATOR ERGONOMICS

Ergonomic handle shape Simple push forward – pull reverse handle control Mechanical lever hopper dump Adjustable handle height (3 positions, tools required)

DUST CONTROL SYSTEM

Filter area 49 ft² | 4.6 m²

Base dust filtration (seasoned filter) 3 microns @ 99% efficiency

HEPA filter 0.3 microns @ 99.97% efficiency

Vacuum fan speed 2000 rpm

Vacuum fan motor 1 hp | 0.75 kW

Vacuum fan diameter 9 in | 230 mm

Shaker mechanism Automatic timed

SOUND LEVEL

Operator's ear 73 dBA

Sound pressure level tested per ISO 11201 as recommended by the AACEM and OSHA

MACHINE DIMENSIONS

Length	63 in 1,600 mm
Width	36.5 in 925 mm
Height	
Handle in lowest position	37 in 940 mm
Handle in middle position	39.5 in 1,000 mm
Handle in highest position	42 in 1,070 mm
Weight	599 lb ∣ 272 kg
Minimum Aisle Turn (left)	68 in 1,730 mm

PRODUCT FEATURES

Heavy-duty wrap-around bumper
Automatic filter shaker
Mechanical lever hopper dump
Thermo-Sentry™
On-board "smart" charger
Adjustable handle height (3 positions, tools required)
Variable forward and reverse propel
Battery discharge indicator
Hour meter
Parking brake
No tool main brush change



us Safety certification

WARRANTY

Please see to your local Tennant representative for information.

Specifications subject to change without notice.

For a complete selection of genuine Tennant brushes and pads, please consult the S10 Parts and Consumables Reference Guide.