## VACUUM SELECTION GUIDE



	V-LWU-13	V-SMU-14	V-DMU-14	V-WA-30
	TATOM MARKET.			
APPLICATIONS*/ ATTRIBUTES				
Description	13 in / 330 mm Light-weight upright vacuum	14 in / 355 mm Single-motor upright vacuum	14 in / 355 mm Dual-motor upright vacuum	30 in / 762 mm Wide-area upright vacuum
Carpet Floors	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>
Hard Floors	Best	Good	Best	Good
Facility Size / Layout	≤ 1,000 ft² / 93 m² Many obstacles	≤ 5,000 ft² / 465 m² Many obstacles	≤ 5,000 ft² / 465 m² Many obstacles	≥ 5,000 ft² / 465 m² Hallways/Open Area
Amount Of Detail Work		Light to Moderate	✓ Moderate to Intense	
Noise-sensitive / LEED Environment (<70 dBa)	<b>✓</b>	<b>~</b>	<b>✓</b>	<b>✓</b>
HEPA Filtration Standard	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>
CRI Seal Of Approval Certified	COLD	SILVER	CHARGE STATE	BRONZE

<sup>\*</sup> These are "best suited for" applications as a general guide, specific customer needs may vary